V-Strom 1050 Specification

| v-strom 1050 Specification | |
|----------------------------|--|
| Overall length | 2,265mm |
| Overall width | 870mm |
| Overall height | 1,515mm |
| Wheelbase | 1,555mm |
| Ground clearance | 165mm |
| Seat height | 855mm |
| Kerb weight | 236kg |
| Engine type | Four-stroke, liquid-cooled, DOHC 90° V-Twin |
| Bore x stroke | 100.0mm x 66.0mm |
| Engine displacement | 1037cc |
| Peak power | 107PS @ 8,500rpm |
| Peak torque | 100N-m/6,000rpm |
| Compression ratio | 11.5 : 1 |
| Fuel system | Fuel injection |
| Starter system | Electric |
| Lubrication system | Wet sump |
| Transmission | Six-speed constant mesh |
| Suspension - front | Inverted telescopic, coil spring, oil damped |
| Suspension - rear | Link type, coil spring, oil damped |
| Rake / trail | 25° / 109mm |
| Brakes - front | Disc, twin |
| Brakes - rear | Disc |
| Tyres - front | 110/80R19M/C 59V |
| Tyres - rear | 150/70R17M/C 69V |
| Ignition system | Electronic ignition |
| Fuel tank capacity | 20 litres |
| Fuel efficiency | 57.65mpg |
| Oil capacity (overhaul) | 3.5 litres |
| | |